


# Headlamp Extension Bracket Kit

## PARTS LIST



98330 Headlamp Extension Bracket Kit							
Item	Part	Qty	Description	Item	Part	Qty	Description
1		1	Headlamp Extension Bracket – DS	4	91105	4	1/2" Flat Washer
2		1	Headlamp Extension Bracket – PS	5	91335	2	1/2-13 Hex Locknut GB
3	90575	2	1/2-13 x 1-1/4 Hex Cap Screw G5	6	93148	4	1/4 x 3/4 Self-Tapping Screw

G = Grade

### ⚠ CAUTION

Read this document before installing the Headlamp Extension Bracket Kit.


### ⚠ CAUTION

Use standard methods and practices when attaching snowplow and installing accessories including proper personal protective safety equipment.


## INSTALLATION INSTRUCTIONS

- Using the outermost mounting hole on the extension bracket, mount the brackets to the existing headlamp mounting holes in the light tower tube with the 1/2" x 1-1/4" cap screws, 1/2" washers and 1/2" locknuts as shown.


- With the 1/2" cap screw installed, level the headlamp extension bracket prior to fully tightening the locknut to 75 ft-lb.



- Using the extension bracket as a guide, locate and drill four 5/32" pilot holes.




Insert a 1/4" x 3/4" self-tapping screw in each hole. Tighten all fasteners and mount the headlamps as described in the Mounting Headlamps to Extension Brackets section of these instructions.



### Mounting Headlamps to Extension Brackets

Place the headlamp swivel plate onto the headlamp mounting studs and place the lamp onto the extension bracket. Mount using a 1/2" lock washer and 1/2" hex nut on the inside hole of the extension bracket, and a 1/2" washer, 1/2" lock washer and 1/2" hex nut on the outside slotted hole of the extension bracket as shown below. Shaded items are included in the headlamp kit.



Headlamps are to be aimed as instructed in the Owner's Manual for the snowplow or in the Headlamp Aiming Instructions found in the headlamp kit.

Copyright © 2008 Douglas Dynamics, L.L.C. All rights reserved. This material may not be reproduced or copied, in whole or in part, in any printed, mechanical, electronic, film or other distribution and storage media, without the written consent of Blizzard. Authorization to photocopy items for internal or personal use by the Blizzard outlets or snowplow owner is granted.

Blizzard reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Blizzard or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle ratings with a snowplow. Blizzard offers a limited warranty for all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, L.L.C.: BLIZZARD®.